

PROUDLY DISTRIBUTED BY:



gaspares.com.au

f GASpares

SUPASWIFT

HOME OWNER RANGE FEATURES

- Large 50 L Grass catcher
- > Sturdy pressed steel chassis
- > 18" (460 mm) Cut
- > One-piece lower handle for strength and support
- Ideal for small to medium sized lawns



COMMERCIAL RANGE FEATURES

- Large grass catcher (65 litre capacity)
- > Aluminium chassis that is durable and impact resistant
- > 20" (508 mm) Cut
- 4 Swing back blades
- 12 Position steel height adjuster
 - 7.5" (190 mm) wheels fitted with double ball bearings



UTILITY RANGE FEATURES

- Big & Little Bob models
- Side discharge pressed steel chassis
- 4 Swing back blades
- 12 Position steel height adjuster
- 7.5" (190 mm) wheels fitted with double ball bearings
- > Ideal for conditions where catching is not required.





HOME OWNER RANGE										
MODEL	ENGINE	CC	CUTTING DECK	CUT	BLADES	DISCHARGE	DRY WEIGHT	WARRANTY*		
SSU775AC	Loncin OHV	140 cc	18" Pressed steel chassis	460 mm	2 Swing back blades	Rear	36.5 kg	Domestic 2 years		
SSU777AMC	Loncin OHV	140 cc	18" Pressed steel chassis	460 mm	4 Swing back blades	Rear	36 kg	Domestic 2 years		
SSU777ASP	Loncin OHV	140 cc	18" Pressed steel chassis	460 mm	4 Swing back blades	Rear	40 kg	Domestic 2 years		
SSU777HMC	Honda GCV160 vertical shaft engine	160 cc	18" Pressed steel chassis	460 mm	4 Swing back blades	Rear	35 kg	Domestic 2 years		
SSU777KMC	KOHLER® Courage® XT675 engine.	149 cc	18" Pressed steel chassis	460 mm	4 Swing back blades	Rear	35 kg	Domestic 2 years		
SSU777KSP	KOHLER® Courage® XT675	149 cc	18" Pressed steel chassis	460 mm	4 Swing back blades	Rear	39 kg	Domestic 2 years		

COMMERCIAL RANGE										
MODEL	ENGINE	CC	CUTTING DECK	CUT	BLADES	DISCHARGE	DRY WEIGHT	WARRANTY*		
SSU797HMC	Honda GXV160	163 cc	20" Aluminium chassis	508 mm	4 Swing back blades	Rear	46.5 kg	Domestic 4 years. Commercial 2 years. Hire 90 Days.		
SSU797KMC	KOHLER® XT775	173 cc	20" Aluminium chassis	508 mm	4 Swing back blades	Rear	46.5 kg	Domestic 4 years. Commercial 2 years. Hire 90 Days.		

UTILITY RANGE										
MODEL	ENGINE	CC	CUTTING DECK	CUT	BLADES	DISCHARGE	DRY WEIGHT	WARRANTY*		
SSU645AP	Loncin OHV	140 cc	18" Pressed steel chassis	460 mm	4 Swing back blades	Side	30 kg	Domestic 2 years. Commercial 6 months. Hire 90 days.		
SSU645HP	Honda GCV160	160 cc	18" Pressed steel chassis	460 mm	4 Swing back blades	Side	30 kg	Domestic 2 years. Commercial 6 months. Hire 90 days.		
SSU645KP	KOHLER® XT675 engine	149 cc	18" Pressed steel chassis	460 mm	4 Swing back blades	Side	30 kg	Domestic 2 years. Commercial 6 months. Hire 90 days.		
SSU653HP	Honda GXV160	163 cc	21" Pressed steel chassis	533 mm	4 Swing back blades	Side	38 kg	Domestic 2 years. Commercial 6 months. Hire 90 days.		
SSU653KP	KOHLER® XT775	173 cc	21" Pressed steel chassis	533 mm	4 Swing back blades	Side	35 kg	Domestic 2 years. Commercial 6 months. Hire 90 days.		

*For further Warranty details please visit gaspares.com.au



SUPASWIFT

CYLINDER RANGE FEATURES

- Loncin OHV 163 cc (3.6 kW) engine featuring low oil cut out
- Large 3.6 litre fuel tank
- Chain drive
- > Adjustable cutting height of 7 30 mm
- Metal grass catcher
- > Hardened bed knife for long lasting quality of cut

CYLINDER RANGE

MODEL	ENGINE	CC	CUTTING DECK	CUT	BLADES	DISCHARGE	DRY WEIGHT	WARRANTY*
SSU417ACM	Loncin OHV	163 cc	17" Steel	430 mm	6 Blade cutting reel	Rear	82 kg	Domestic 4 years. Commercial and Hire 90 Days.
SSU420ACM	Loncin OHV	163 cc	20" Steel	500 mm	6 Blade cutting reel	Rear	84 kg	Domestic 4 years. Commercial and Hire 90 Days.





SSU420ACM featured

SWIFE

*For further Warranty details please visit gaspares.com.au

- Horizontal & vertical operation
- Auto return valve
- Tow Hitch*: 2" (50 mm) ball hitch with safety chains Aust style trailer bail hitch
- Maximum Log Length: 25" (635 mm)
- > 12" x 4.80" multi lug trailer wheel
- > High angled heat treated steel wedge

LOG SPLITTER RANGE

MODEL	ENGINE	CAPACITY	BEAM	CYCLE TIME	PUMP	WEDGE	HYDRAULIC TANK CAP.	RAM SIZE
SSU525KLS	KOHLER® SH Series™ SH265 single cylinder OHV (6.5 hp / 4.8 kW / 196 cc) engine	25 Tons of splitting force	8.5" (215.9 mm) Foot plate	10.9 seconds (down and back)	Two stage 13 GPM (49.21 litres per minute)	8.5 " (215.9 mm) High angled heat treated steel	26.49 litres	1.75" (44.45 mm) Dia.
SSU530KLS	KOHLER® Command PRO® CH395 single cylinder OHV (9.5 hp / 6.8 kW / 277 cc) engine	30 Tons of splitting force	9" (228.6 mm) Foot plate	12.9 seconds (down and back)	Two stage pump 17.5 GPM (66.24 litres per minute)	9" (228.6 mm) High angled heat treated steel	45.42 litres	2" (50.8 mm) Dia

