

ManagementHorwood Bagshaw

Compact Scaribar

Compact Scaribar - Evolutionary Design for the Small Farmer.



Horwood Bagshaw's Compact Scaribar minimises the need for a tractor upgrade.

You can trust
Horwood Bagshaw to
provide machinery which
is durable and reliable.
With robust design and
high quality engineering,
the Compact Scaribar
has been developed
specifically to cater
for farmers looking
for a smaller, more
versatile machine.

Evolutionary Design for the Small Farmer

The Compact Scaribar is a 'No-Till' machine which provides the ideal upgrade from combines.

The innovative design allows it to be used by relatively low horsepower tractors (from 120hp) so it minimises the need for a tractor upgrade.

Compact Design for Tight Paddocks/Bays

Horwood Bagshaw understands that smaller farmers often have much tighter paddocks to manage. That's why the new Compact Scaribar has been designed with a shorter A frame.

This allows manageable turning and greater manouevrability in general.

Narrow gates are no problem with the 3m transport width.

Narrowest Transport Width (3m)

No more loading combines onto trucks! No more escorts required!

In order to comply with tougher road transport regulations, the Compact Scaribar has a very narrow 3 metre transport width.

This increases safety when travelling along narrow roads and means less 'pruning' of tree-lined tracks.

It comes fitted with 16 ply tyres, suitable for most road and soil conditions.



Folded 3m transport width with tow-behind airseeder.



Folded 3m transport width with mounted airseeder.

There's no substitute for quality $^{^{TM}}$

Big (No Till) Machine Performance

Tough, Strong and Reliable. That's what you can expect from any Horwood Bagshaw machine.

The Compact Scaribar is no exception, using the same proven frame design and quality components of the larger models.

Its multi-purpose features - cultivator; primary tillage; and no till seeding rig - make it an ideal contractor's machine.

Unmatched Choice of Tine Spacings

Horwood Bagshaw's Compact Scaribar is particularly versatile.

The one frame can accommodate five spacing options to suit the varying needs of farmers.

- 7" (80mm) for those growers who want to sow hay/pasture for feed
- 8³/₄" (225mm)
- 10" (250mm) or 12" (300mm)
- for those with cropping or guidance programmes that require a wider spacing.
- 13¹/₃" (333mm) will particularly appeal to Control Traffic Farmers.

Comprehensive range of Tines

A range of tines is available to suit individual farming applications; whether primary or secondary tillage, chisel ploughing, direct drilling or row cropping; whether in light, heavy or rocky soils:

- Tine Breakout from 75lbf to 660lbf
- Spring Tine
- Hydraulic Tine
- · Tine Shanks
- Edge-on C Shank
- Edge-on Straight Shank
- Flat-on C Shank

Ideal Control Traffic/ Raised Bed machine

The Compact Scaribar has a 2m wheel track to suit raised beds and controlled traffic operations.

Extensive range of matching Airseeders

The Compact Scaribar can be used in conjunction with a range of airseeders:

- A frame mounted 2000/2500 litre models
- Tow Behind (2m track) 3000, 4000/4500 litre or 6000/7000 litre models.

Clever Mechanical Design

Other clever design features of the Compact Scaribar include:

- A Torsion Tube which provides level lift to facilitate 'Set & Forget' front and rear levelling
- Split Hydraulics for easy levelling and increased lifting capacity for framemounted presswheels and harrows.



Compact Scaribar with A Frame mounted airseeder.

	Centre Frame 9'10" (3.0m)	Broadacre Models						Controlled Traffic Models				
Compact Centre		19' (5.8m)	20' (6.1m)	23' (7.0m)	26′ (7.9m)	28' (8.5m)	29' (8.8m)	19' (3 bed	20' (6.1m)	23' (7.0m)	26' (4 beds)	28' (8.5m)
NUMBER OF TINES (set of	n 5 rows)											
At 7" spacings At 8 ³ / ₄ spacings	(180mm) (225mm)	33	27	39 31	35		49 39	33				
At 10" spacings At 12" spacings	(250mm) (300mm)	23 19	24	27/28 23	32	34	35 29	23 19	24	28	32	34
At 13 ¹ / ₃ " spacings	(333mm)	18		20	24		26	18		20	24	26
FRAME DIMENSIONS												
Height	(transport)	12'10" (3.9m)	12"10" (3.9m)	12'10" (3.9m)	14'2" (4.3m)	15'8" (4.8m)	15'8" (4.8m)	12′1((3.9m		12'10" (3.9m)	14'2" (4.3m)	15'8" (4.8m)
Width	(transport)	9'10" (3.0m)	9'10" (3.0m)	9'10" (3.0m)	9'10" (3.0m)	9'10" (3.0m)	9'10" (3.0m)	9′10 (3.0m		9'10" (3.0m)	9'10" (3.0m)	9'10" (3.0m)
Length	A Frame Length	9'10"	9'10"	9'10"	9'10"	9'10"	9'10"	9′10	" 9'10"	9'10"	9'10"	9'10"
	Main Frame Depth	11′2″	11′2″	11′2″	11′2″	11′2″	11′2″	11′2	" 11′2″	11′2″	11′2″	11′2″
	Total Length	21'0" (6.4m)	21'0" (6.4m)	21'0" (6.4m)	21'0" (6.4m)	21'0" (6.4m)	21'0" (6.4m)	21′0 (6.4m		21'0" (6.4m)	21'0" (6.4m)	21'0" (6.4m)
WEIGHT Bare	(at 7" spacing) kg	3800	3300	4500	3850	3950	5000	380	3300	4500	3850	3950
TYRES		•				1	2.5/80 x 18 (1	δ ply) —				\longrightarrow



9 Adelaide Road, Mannum, South Australia 5238 Phone: (08) 8561 6200 Fax: (08) 8561 6205 Email: general@horwoodbagshaw.com.au Web: www.horwoodbagshaw.com.au



Clever wing fold and 2m wide track enable safer transport between sites.

There's no substitute for quality $^{\text{\tiny TM}}$

